

# Consistent excellence for bioanalysis





# SOLAµ - delivering reproducible low volume extractions. Everytime!

Thermo Scientific™ SOLAµ™ plates are designed for bioanalytical and clinical research analyst's who require cleaner, highly reproducible and robust sample extraction at very low sample and solvent volumes in high throughput workflows. SOLAµ achieves this due to the unique and innovative frit-less SPE technology.

SOLAµ is the first micro elution product to truly meet the requirements of the bioanalyst.

## Pharmaceutical and Biopharmaceutical analytical challenges

The modern bioanalytical and clinical research laboratory must provide high quality analytical results from complex biological samples in a high throughput environment while complying with strict legislation.

These demands are compounded by the continued drive to higher efficacy drugs and long acting formulations which continue to push the required quantification limits to lower levels. There is also the desire to take advantage of the replacement, refinement and reduction policy. The growth of biopharmaceuticals also brings into consideration additional analytical challenges such as solvation and non-specific binding.


## What is required of the bioanalyitcal method to meet these demands?

- Robustness low analytical failure rates
- Ability to process low sample volumes
- High sensitivity
- High reproducibility
- Ease of use
- High throughput processing
- Ffficient and fast

## The micro elution SPE format is uniquely positioned to deliver on these requirements.

The proprietary SOLA manufacturing process generates an SPE micro elution product which eliminates the issues with traditional loose-packed micro elution formats. By combining the support material and active media components into a solid uniform sorbent bed we remove the need for frits (Figure 1).

Stable and controllable flow through the SPE micro elution device is another key factor controlling reproducibility of the final analytical method. This is especially important in low bed weight devices where flow control is more difficult due to lower back pressure from the sorbent. The macro-porous structure found within SOLAµ is defined by a well controlled, reproducible manufacturing process which results in uniformity well to well, plate to plate and batch to batch. This provides an added advantage when dealing with viscous biological samples, preventing blocking and enabling high throughput processing of samples.




## SOLAµ provides you with reproducible sensitivity


## Concentration of a large sample volume to achieve quantitation limits

Up to 20 times increase in sensitivity can be achieved by loading a large volume of sample and eluting in a low volume.

In the following example 500  $\mu$ L human plasma was loaded onto the SOLA $\mu$  plate for the analysis of niflumic acid. The compound was eluted in 25  $\mu$ L providing a 20 times increase in concentration whilst maintaining excellent precision.



Sample enrichment (20 x pre-concentration)



	Precision Data for Niflumic Acid Peak Area Ratio (%RSD) n = 18	Recovery of Niflumic Acid (%)	Matrix Effects (%)
QC Low (0.4ng/mL)	1.31	89.9	8.63
QC high (30ng/mL)	1.06	94.0	3.21

## Sample preparation protocol

## Sample pre-treatment

 $500~\mu\text{L}$  of human plasma diluted 1:1 with 4% phosphoric acid

		ation

Compound(s):	niflumic acid, niflumic acid d5 (IS)	
Matrix:	human plasma	
	SOLAµ WAX 96 well plate (60209-005)	
Condition:	200 μL methanol	
Equilibrate:	200 μL 4% phosphoric acid	
Load:	apply sample at 0.5 mL/min	
Wash:	200 µL 25 mM ammonium acetate (pH4)	
	200 μL 70% methanol (pH4)	
Elute:	$2\times12.5~\mu\text{L}$ 50/50 methanol/acetonitrile with 2% ammonia	

### Direct injection of eluent


Direct injection of clucift		
HPLC system:	Thermo Scientific™ Dionex™ UltiMate™ 3000 RSLC system	
Column:	Thermo Scientific™ Accucore™ RP-MS HPLC column 50 mm $\times$ 2.1 mm 2.6 $\mu$ m (17626-052130)	
Guard column:	Thermo Scientific™ Accucore™ RP-MS Defender™ guard cartridge (17626-012105) Thermo Scientific™ Uniguard™ drop-in guard holder (852-00)	
Mass spec system:	Thermo Scientific™ TSQ Vantage™ Triple Stage Quadruple mass spec	

Precision, recovery and matrix effects data for niflumic acid at Low QC 10 ng/mL and High QC 750 ng/mL (n=18)


## Sample limited assays or scaling down a conventional SPE method and obtaining equivalent sensitivity

SOLAµ allows users to directly scale down the volumes used in their analytical methods, allowing for a reduction in sample usage and eliminating issues caused by evaporation without compromising the sensitivity of their assay. This is also an important consideration when sample volumes are limited.

The following example shows that by loading 25 µL of niflumic acid sample onto the SOLAµ plate and eluting in a total of 25 µL a ten-fold decrease in sample volume was achieved when compared to a traditional scale higher bed weight product. Equivalent method performance and high levels of reproducibility provided by SOLA technology were still maintained.



Equivalency of results obtained with niflumic acid (500 ng/mL) extracted with 10 mg SOLA WAX using 250 µL of sample and SOLAµ WAX using 25 µL of sample.



### Sample preparation protocol

### Sample pre-treatment

500 µL of human plasma diluted 1:1 with 4% phosphoric acid

C	-1-			
Sam	me	nre	บลเล	шоп

Direct injection o	f eluent
Elute:	$2 \times 12.5 \mu L$ methanol with 2% ammonia
	200 μL methanol
Wash:	200 µL 25 mM ammonium acetate (pH4)
Load:	apply 25 µL sample at 0.5 mL/min
Equilibrate:	200 μL water
Condition:	200 μL methanol
	SOLAµ WAX 96 well plate (60209-005)
Matrix:	human plasma
Compouna(s):	nitiumic acid, nitiumic acid d5 (i5)

Direct injection of eluent		
HPLC system:	Thermo Scientific™ Dionex™ UltiMate™ 3000 RSLC system	
Column:	Thermo Scientific™ Accucore™ RP-MS HPLC column 50 mm $\times$ 2.1 mm 2.6 $\mu$ m (17626-052130)	
Guard column:	Thermo Scientific™ Accucore™ RP-MS Defender™ guard cartridge (17626-012105) Thermo Scientific™ Uniguard™ drop-in guard holder (852-00)	
Mass spec system:	Thermo Scientific™ TSQ Vantage™  Triple Stage Quadruple mass spec	

## **Precision Data for Niflumic Acid**


	Analyte Peak Area (%RSD)	Peak Area Ratio (%RSD)
Low QC	7.32	0.356
High QC	5.33	0.195

Precision data niflumic acid at Low QC 10 ng/mL and High QC 750 ng/mL (n=18)


## Extracting samples which are susceptible to solvation and non-specific binding issues

With traditional SPE the eluted sample is typically blown down to increase the concentration of the sample and thus improve the sensitivity. This causes an issue for certain compound types which can be lost during this step resulting in reduced sensitivity. SOLAµ allows the sample to be extracted without the need for dry down and reconstitution. Not only does this maximize recovery of the analytes it also improves workflow efficiency and increases productivity.

In the case of extraction of ibuprofen a four-fold pre-concentration was achieved without the need for dry down by loading 200  $\mu$ L of sample onto the SOLA $\mu$  plate and eluting in a total of 50  $\mu$ L. The results demonstrate that even with this low elution volume, excellent reproducibility was achieved.



Example chromatogram at quantitation limit of 10 ng/mL for ibuprofen



### Sample preparation protocol

### Sample pre-treatment

 $200\,\mu\text{L}$  of human plasma diluted 1:1 with 4% phosphoric acid

Compound(s):	ibuprofen, ibuprofen d3 (IS),
Matrix:	rat plasma
	SOLAµ SAX 1 mL 96 well plate (60109-002)
Conditioning:	200 μL methanol
	200 μL water
Application:	load sample at 0.5 mL/min
Washing:	200 μL water with 1% NH4
	200 μL methanol with 1% NH4
Elution:	$2\times25~\mu\text{L}$ 50/50 methanol/acetonitrile with 2% formic acid
Dilution:	add 50 µL water to each sample

Dilution:	add 50 µL water to each sample	
Direct injection of	eluent	
HPLC system:	Thermo Scientific™ Dionex™ Ultimate™ 3000 RS system	
Column:	Accucore RP-MS 50 mm × 2.1mm 2.6 µm (17626-052130)	
Guard column:	Accucore RP-MS defender (17626-012105) Uniguard drop-in guard holder (852-00)	
Mass spec system:	Thermo Scientific™ TSQ Vantage™ Triple Stage Quadruple mass spec	


	lbuprofen (%RSD) n=18	lbuprofen recovery (%)
Low QC (25 ng/mL)	4.00	90
High QC (750 ng/mL)	1.70	95

Precision data for ibuprofen at Low QC 25 ng/mL and High QC 750 ng/mL (n=18)

## SOLAµ loading capacity

The utilization of our advanced polymeric technologies in SOLAµ provides an SPE phase with excellent loading capacity. This ensures that good retention of analyte and removal of matrix interferences is achieved when a larger range of sample volumes are applied.

In the following example incremental volumes of human plasma spiked at 200 ng/mL with a polar (atenolol) and non polar (imipramine) analyte were extracted. Recovery and matrix effects were monitored across the loading range to demonstrate acceptable assay performance.



## **Conclusion**

SOLAµ meets bioanalyitcal needs by providing:

- A robust low sample volume preparation platform
- Reproducibility at low sample and solvent levels
- Processing of low volume samples
- Sample enrichment (20 times)
- Mitigates against solvation and non-specific binding issues

## Ordering information

Description	Part Number
SOLAµ HRP 96 well plate	60209-001
SOLAµ SCX 96 well plate	60209-002
SOLAµ SAX 96 well plate	60209-003
SOLAµ WCX 96 well plate	60209-004
SOLAµ WAX 96 well plate	60209-005



Description	Part Number
HyperSep-96 Well Plate Manifold	60103-351
Vacuum Pump, European Version	60104-241
Vacuum Pump, North American Version	60104-243



## A comprehensive product offering for your complete bioanalytical workflow

## **Sample Preparation**



Separation



Sample Handling



**Detection** 



LC Columns



**Data Processing** 



## thermoscientific.com/sola-spe thermoscientific.com/chromatography

© 2014 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries. This information is presented as an example of the capabilities of Thermo Fisher Scientific products. It is not intended to encourage use of these products in any manners that might infringe the intellectual property rights of others. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

USA and Canada +1 800 332 3331 Australia 1300 735 292 (free call domestic) China 800 810 5118 (free call domestic) 400 650 5118

France +33 (0)1 60 92 48 34 Germany +49 (0) 2423 9431 20 or 21 India +91 22 6742 9494 +91 27 1766 2352

**Japan** 0120 753 670 (free call domestic) 0120 753 671 fax

United Kingdom +44(0) 1928 534 110

New Zealand 0800 933 966 (free call domestic)

Singapore +65 6289 1190

**All Other Enquiries** +44 (0) 1928 534 050

Technical Support For advice and support, please visit our website: www.thermoscientific.com/chromexpert



A Thermo Fisher Scientific Brand