



RESIN INFORMATION SHEET

Product Name	TOYOPEARL® Ether-650 (Hydrophobic interaction chromatography resin)		
Part Numbers	0043151 TOYOPEARL Ether-650S, 2		i mL
	0016172	TOYOPEARL Ether-650S, 100 mL	
	0016174	TOYOPEARL Ether-650S, 1 L	
	0016176	TOYOPEARL Ether-650S, 5	L
	0019805	TOYOPEARL Ether-650M, 25 mL TOYOPEARL Ether-650M, 100 mL	
	0016173		
	0016175	TOYOPEARL Ether-650M, 1	L
	0016177 TOYOPEARL Ethe		L
Product Description	TOYOPEARL chromatographic resins are based on a rigid methacrylic polymer, resulting in high mechanical and chemical stability. Resins are available as non-functionalized "HW" series resins for size exclusion separations, and derivatized with surface chemistries for alternative modes of chromatography such as ion exchange, hydrophobic interaction or affinity separations. TOYOPEARL Ether-650 chromatographic resins are designed for hydrophobic interaction chromatography. This chromatographic mode separates molecules on the basis of hydrophobic interactions between the sample and the ligand. The separation is usually accomplished in buffered aqueous solution with a gradient of decreasing ionic strength.		
Operating	Packing pressure		Typically 0.3 MPa
Conditions	Shipping solvent		20 % (v/v) ethanol
	Shipping formulation		72 % (v/v) slurry in shipping solvent (*)
	Pressure limiting factor		Depend on column hardware (typically 0.7 MPa)
	Operating linear flowrate		Typically 10 - 600 cm/hour
	Long-term storage conditions		20 % (v/v) ethanol
	Cleaning-in-place/Sanitization		0.1 - 0.5 mol/L NaOH or 0.1 mol/L HCl
Specifications	Particle size distribution (min. 80 % within range)		20 - 50 µm for S-grade 40 - 90 µm for M-grade
	Protein adsorption capacity (of lysozyme)		10 - 30 g/L
	Bacterial count		Max. 100 CFU/mL
	Endotoxin concentration		Max. 10.0 EU/mL
	Eluable matter		Max. 0.2 % (for dry gel)
	Foreign substance (colored particle)		Unobserved
Additional	Appearance		White resin slurry which settles upon standing

100 nm (*)

(*) The value is for reference only, not guaranteed.

Lot-specific data are included in the Certificate of Analysis (COA) shipped with the product. For detailed test procedures please refer to the appropriate Regulatory Support File.

Mean pore diameter (base resin)

Information